



## SPECIFICATION

**Product Name :** Face Recognition SAS-AI06

**Screen :** 4.3 Inch, HD 272"480, Capacitive Touch Screen

**Operation system :** LINUX 3.10

**CPU.NPU :** 1.2G Dual-Core ARM Cortex-A7, 600G (0.6T)1GB

**RAM :** 256MB DDR3

**ROM :** eMMC Flash 4GB

**Binocular camera :** 200W Colorful WDR+200W Infrared live camera

**Face Recognition Accuracy :** 99.70%

**Recognition Distance :** 0.5-2.5 meters

**Working Style :** Online

**Prevent Photo :** Dual camera anti-counterfeiting prevents recognition with photo/video

**USB :** USB2.0 x1, Supports U disk import/export data

**Power supply :** DC12V interface x 1

**Speaker Interface :** Reserved for extended Speaker Interface

**Network Communication :** TCP/IP Support C/S LAN communication, USB

**Free Attendance software :** Support exporting excel attendance report with U disk

**Shift :** Support shift setting and importing shift schedule -U disk

## FACE RECOGNITION ACCESS CONTROL SYSTEM

India's Most Trusted, Sold  
Best in Class, Fully Loaded

## FEATURES

- 4.3 -inch 272"480, Capacitive Touch Screen
- 200W Colorful WDR+200W Infrared live camera
- Adjusts supplement light brightness manually
- Face recognition in a dark environment
- Face recognition distance: 0.5 to 1.5m
- Deep learning algorithm
- 5,000 face capacity 5,000 Card and 5,00,000 Log capacity
- Multiple authentication modes
- Face recognition duration 0.25 seconds
- Stand-alone operation
- Transmits data to the client software via TCP/P Support C/S LAN communication, USB & saves the data on the client software
- Capture linkage and captured pictures saving
- Imports data to the device from the client software
- Manage, search & set device data after logging in to the device locally



**SAS-AI06**



Face



Card